

AMENDMENTS TO THE CLAIMS

1. (currently amended) A pump system for a personal care appliance, comprising:

a fluid cartridge member ~~made of flexible material~~, the fluid cartridge member having a flexible fluid-filled portion and an exit opening for the fluid in the cartridge, for delivery to a line which connects to a workpiece portion of the appliance;

a base member having a cutout portion into which the fluid-filled portion of the cartridge member can nest; and

a pressing member, at least a nesting portion of which has a length and diameter which substantially match the cross-section of the cutout portion of the base member, ~~such that, over for~~ at least a substantial portion of the length of the cutout portion, ~~the fluid-filled portion and the pressing member substantially next with the cutout portion; wherein the nesting portion of the pressing member directly contacts the fluid-filled cartridge portion continuously across substantially the entire cutout portion, wherein the pressing member includes two mounting elements which extend outwardly from the opposing ends of the nesting portion sufficiently that the pressing member is movable by action on the mounting elements,~~ so that as the pressing member is moved in operation forwardly over the cartridge, fluid is moved from the fluid-filled portion through the exit opening, with the flexible cartridge portion being flattened during such action substantially without creasing of the cartridge.

2. (previously presented) The system of claim 1, wherein the pressing member is moved by user action.

3. (cancelled)

4. (currently amended) The system of claim 3, wherein the nesting portion of the pressing member is configured to nest with the cutout portion around its entire circumference, permitting the nesting portion to roll along the fluid-filled portion of the cartridge, pressing fluid out therefrom through the exit opening.

5. (currently amended) A pump system for a personal care appliance, comprising:

a fluid cartridge member made of flexible material, the fluid cartridge member having a fluid-filled portion and an exit opening for the fluid in the cartridge, for delivery to a line which connects to a workpiece portion of the appliance;

a base member having a cutout portion into which the fluid-filled portion of the cartridge member can nest; and

a pressing member, at least a nesting portion of which has a configuration which substantially matches the cross-section of the cutout portion of the base member, such that, over at least a substantial portion of the length of the cutout portion, the fluid-filled portion and the pressing member can substantially nest with the cutout portion, so that as the pressing member is moved in operation forwardly over the cartridge, fluid is moved from the fluid-filled portion through the exit opening, with the flexible cartridge being flattened during such action substantially without creasing of the cartridge,

wherein the fluid cartridge includes a reservoir portion from which fluid moves to replenish fluid in the fluid-filled portion after a dispensing action.

6. (previously presented) The system of claim 5, wherein the fluid-filled portion comprises a material which inflates after being compressed by the pressing member, such that fluid from the reservoir moves into the empty part of the fluid-filled portion by vacuum action.

7. (previously presented) The system of claim 5, including means for pressuring the reservoir so that fluid is moved into the emptied part of the fluid-filled portion behind the pressing member as the pressing member moves along its path.

8. (previously presented) The system of claim 1, wherein a beginning part of the cutout portion is narrower than the length of the nesting portion of the pressing means but tapers outwardly to a point where the nesting portion fully nests within the cutout portion.

9. (previously presented) The system of claim 1, wherein an end part of the cutout portion tapers inwardly such that as the pressing member moves along its path, it is lifted upwardly from the base member and out of nesting contact with the cutout portion.

10. (currently amended) The system of claim 9 1, including a support arm member which is arranged and operative to support the pressing member for a return of the pressing member to a start point of its pressing action.

11. (previously presented) The system of claim 10, wherein return of the pressing member is by spring action.

12. (currently amended) A power toothbrush, comprising:

a handle portion having a driving system and a power supply for the ~~driver~~ assembly driving system;

a driven member assembly having an arm on which a brushhead is mounted and a structural element for connecting the driven member assembly to the ~~handle element~~ driving system;

a pump system for dispensing fluid to the brushhead, the pump assembly including a fluid cartridge member ~~made of flexible material, the fluid cartridge member~~ having a flexible fluid-filled portion and an exit opening for the fluid in the cartridge, for delivery to a line which connects the pump to the brushhead;

a base member having a cutout portion into which the fluid-filled portion of the cartridge member can nest; and

a pressing member, at least a nesting portion of which has a length and a diameter which substantially match the cross-section of the cutout portion of the base member, ~~such that, ever for~~ at least a substantial portion of the length of the cutout portion, ~~the fluid-filled portion and the pressing member substantially nest with the cutout portion, wherein the nesting portion of the pressing member directly contacts the fluid-filled cartridge portion continuously across substantially the entire cutout portion,~~ so that as the pressing member is moved in operation over the cartridge, fluid is moved from the fluid-filled portion through the exit opening into the connecting line, with the flexible cartridge portion being flattened during such action substantially without creasing thereof.

13. (currently amended) The toothbrush of claim 12, wherein the pressing member includes two mounting elements which extend outwardly from opposing ends of the nesting portion, sufficiently that the pressing member is movable by action on the mounting elements.

14. (previously presented) The toothbrush of claim 12, wherein the nesting portion of the pressing member is configured to nest with the cutout portion around its entire

circumference, permitting the nesting portion to roll along the fluid-filled portion of the cartridge, pressing fluid out therefrom through the exit opening.

15. (previously presented) The toothbrush of claim 12, including means for pressurizing the reservoir so that fluid is moved into the emptied part of the fluid-filled portion behind the pressing member as the pressing member moves along its path.

16. (currently amended) The system of claim 5, wherein a beginning part of the cutout portion is narrower than the length of the nesting portion of the pressing ~~means~~ member but tapers outwardly to a point where the nesting portion fully nests within the cutout portion.

17. (previously presented) The system of claim 5, wherein an end part of the cutout portion tapers inwardly such that as the pressing member moves along its path, it is lifted upwardly from the base member and out of nesting contact with the cutout portion.

18. (previously presented) The toothbrush of claim 12, wherein the fluid cartridge includes a reservoir portion from which fluid moves to replenish fluid in the fluid-filled portion after a dispensing action.

19. (currently amended) The toothbrush of claim 12, wherein a beginning part of the cutout portion is narrower than the length of the nesting portion of the pressing ~~means~~ member but tapers outwardly to a point where the nesting portion fully nests within the cutout portion.

20. (previously presented) The toothbrush of claim 12, wherein an end part of the cutout portion tapers inwardly such that as the pressing member moves along its path, it is lifted upwardly from the base member and out of nesting contact with the cutout portion.